The Willgo Wheelchair looks like any other more conventional Wheelchair, and can be used in exactly the same way, powering at the Hand Rims. Deciding to travel further the Transmission is engaged, 2 easy motions, the Handles raise automatically, and the Wheelchair is powered away with the User sitting upright, loading against the Back Rest, reducing repetitive strain at wrists and hands, improving breathing and posture. Power is substantially increased. Power can be biased for greater or reduced strength laterally. Clothing and Hands are away from road tyres.



info@willgowheelchairs.com www.willgowheelchairs.com

Anti Tip Tube. Hydraulic Disc Brakes, sensitive braking in wet or dry, maintenance free, adjustable Lever throw and Tension for Users with varying hand grip.



Anti Roll Back, Wheelchair will not roll backwards down an incline while Transmission is engaged. Front Wheel suspension giving lateral stability, reduced shock loading.



Parking Brakes, Scissor action, or Push to Lock. Tyres 25mm smooth, 25mm standard, 30mm knobbly.



Standard Brake set, Pull To Brake set, Push Handles for power forward, Pull Handles to brake, for Users with varying hand grip.



Back Rest Fabric fully adjustable for tension, Back Rest height adjustable through 125mm. Cushion Standard or Posture.



Rear Wheels Quick Release. Toggle engaging and disengaging Transmission. Fully Adjustable Back Rest through 7 degrees forwards rearwards.



Upper Transmission adjusts 2 settings for Users with longer or shorter arms. Lower Transmission adjusts 5 settings for balance. Adjustable Foot Rest.



Frame Cushions at knee and back. Carry Bag 300mm at Seat front. Handles lock down assisting Transit. Handles raise automatically.

Willgo Technica	l and Options					
Weight	-	with wheels -		17kg		
Weight	-	without wheels	-	12kg		
Length	-	back rest folded, wheels fitted	-	860mm		
Width	-	back rest folded, wheels fitted	-	510mm		
Height	-	back rest folded, wheels fitted	-	540mm		
Height	-	back rest up, wheels fitted	-	800mm - 915mm		
Height	-	back rest folded, wheels removed	-	520mm		
Width	-	seat 380mm/15"	-	655mm		
Width	-	seat 430mm/17"	-	705mm		
Back Rest	-	adjustable up down	-	115mm		
Seat Angle	-	7 degrees				
Speed	-	10 kph attainable				
Disc Brakes	-	Willgo, hydraulic, adjustable throw and tension				
Frame	-	Willgo, aluminium, 6061, T6, 25mm x 1.2mm /1.8mm wall				
Transmission	-	Willgo, reciprocating, fully independent laterally				
Rear Wheels	-	Willgo, incorporating drive engagement disengagement lock				
Fabric	-	Willgo, 25mm/50mm back, 50mm seat, adjustable back tension				
Foot Rest	-	Willgo, 400mm - 480mm adjustable height from seat				
Front Wheels	-	Frog Legs, independent suspension				
User Weight	-	maximum user weight 120kg				

<u>Willgo Order Fo</u>	<u>rm</u>						
Seat width measured across the seat from seat tube centres:							
380mm/15″			-				
430mm/17"			-				
Frame		-	Blue -				
Frame		-	Red -				
Frame		-	Green -				
Back Cushion		-	Standard -				
Back Cushion		-	Posture -				
Invoice to:			<u>Deliver to</u> :				
Name:			Name:				
Address:			Address:				
Post Code:							
Т.							
E.							
Warranty -	Frame	-	3 year				
-	Transmission	-	1 year				
-	Other parts	-	1 year	© Willao			